



AKE Containers Non-forkliftable base

The container is a non-welded unit with individual, exchangeable parts, facilitating quick, easy and cost efficient exchange of damaged extrusions and sheets.

General specifications

Design	According to NAS 3610-2K2C; TSO-C90
MGW	3500 lb/1587 kg
Max. dimensions	79/61.5x60.4x64 in.
Internal volume	152 ft ³ / 4.3 m ³



Fabric door options:

- Forkliftable base
- Additional stiffeners
- Spring actuated, self-roll-up fabric door
- 2-door version (walk-through optional)
- Various colours of fabric door
- GOH (Garment on Hangers) transport provision
- Polycarbonate sheets

Part Number	Door Configuration	Tare Weight (typical)
3-B-112	1 fabric door 1-bar	176 lb/80 kg
3-B-212	1 fabric door 2-bar	181 lb/82 kg
3-B-312	1 fabric door 3-bar	183 lb/83 kg



Barless door options:

- Forkliftable base
- Additional stiffeners
- Various colours of fabric door
- GOH (Garment on Hangers) transport provision
- Polycarbonate sheets

Part Number	Door Configuration	Tare Weight (typical)
3-V-112	1 fabric door barless	172 lb/78 kg
3-B-M12	1 fabric door & net	178 lb/81 kg



Metal door options:

- Forkliftable base
- Additional stiffeners
- 2-door version
- GOH (Garment on Hangers) transport provision
- Polycarbonate sheets

Part Number	Door Configuration	Tare Weight (typical)
3-D-218	1 piano hinged metal door	203 lb/92 kg

www.driessen.com

Air Cargo Equipment • Trolleys • Galley Structures
Galley Equipment • First Class Monuments • Crewrests



DRIESSEN

Driessen Europe

De Stek 1,
PO Box 28
1770 AA Wieringerwerf
The Netherlands
Phone +31 227 606 161
Fax +31 227 606 120
Email europe@driessen.com

Driessen USA

3340 C. Greens Rd.
Suite 300
Houston, TX 77032
USA
Phone +1 281 590 0300
Fax +1 281 590 0308
Email houston@driessen.com

Driessen Asia Pacific

Asia Pacific Region Sales Office
4 Loyang Crescent
Singapore 508979
Singapore
Phone +65 65 465 486
Fax +65 65 465 487
Email singapore@driessen.com