



DPE Containers Non-forkliftable base

The container is a non-welded unit with individual, exchangeable parts, facilitating quick, easy and cost efficient exchange of damaged extrusions and sheets.

General specifications

Design	According to AS 1677 (general requirements for non-certified ULDs, B 767)
MGW	2700 lb/1225 kg
Max. dimensions	61.5/47x60.4x64 in.
Internal volume	116.5 ft ³ / 3.3 m ³



Fabric door options:

- Forkliftable base
- Additional stiffeners
- Spring actuated, self-roll-up fabric door
- 2-door version (walk-through optional)
- Various colours of fabric door
- GOH (Garment on Hangers) transport provision
- Polycarbonate sheets

Part Number	Door Configuration	Tare Weight (typical)
2-B-112	1 fabric door 1-bar	150 lb/68 kg
2-B-212	1 fabric door 2-bar	152 lb/69 kg
2-B-312	1 fabric door 3-bar	154 lb/70 kg



Barless door options:

- Forkliftable base
- Additional stiffeners
- Various colours of fabric door
- GOH (Garment on Hangers) transport provision
- Polycarbonate sheets

Part Number	Door Configuration	Tare Weight (typical)
2-V-112	1 fabric door barless	150 lb/68 kg
2-B-M12	1 fabric door & net	148 lb/67 kg



Metal door options:

- Forkliftable base
- Additional stiffeners
- 2-door version
- GOH (Garment on Hangers) transport provision
- Polycarbonate sheets

Part Number	Door Configuration	Tare Weight (typical)
2-D-218	1 piano hinged metal door	169 lb/77 kg