



DQF Containers Non-forkliftable base/Forkliftable base

The container is a non-welded unit with individual, exchangeable parts, facilitating quick, easy and cost efficient exchange of damaged extrusions and sheets.

General specifications

Design	According to AS 1677 (general requirements for non-certified ULDs, B 767)	
MGW	5400 lb/2449 kg	
Max. dimensions	125/96x60.4x64 in.	
Internal volume	247 ft ³ / 7.0 m ³ (non-forkliftable)	233 ft ³ / 6.6 m ³ (forkliftable)



Barless door options:

- Forkliftable base/non-forkliftable base
- Additional stiffeners
- Various colours of fabric door
- GOH (Garment on Hangers) transport provision
- Polycarbonate sheets

Part Number	Door Configuration	Tare Weight (typical)
8-B-N12	1 fabric curtain & net	254 lb/115 kg
8-B-V22	1 fabric curtain & straps	355 lb/161 kg



Metal door options:

- Forkliftable base/non-forkliftable base
- Additional stiffeners
- 2-door version
- GOH (Garment on Hangers) transport provision
- Polycarbonate sheets

Part Number	Door Configuration	Tare Weight (typical)
8-D-218	1 piano hinged metal door	290 lb/131 kg

www.driessen.com

Air Cargo Equipment • Trolleys • Galley Structures
Galley Equipment • First Class Monuments • Crewrests



Driessen Europe

De Stek 1,
PO Box 28
1770 AA Wieringerwerf
The Netherlands
Phone +31 227 606 161
Fax +31 227 606 120
Email europe@driessen.com

Driessen USA

3340 C. Greens Rd.
Suite 300
Houston, TX 77032
USA
Phone +1 281 590 0300
Fax +1 281 590 0308
Email houston@driessen.com

Driessen Asia Pacific

Asia Pacific Region Sales Office
4 Loyang Crescent
Singapore 508979
Singapore
Phone +65 65 465 486
Fax +65 65 465 487
Email singapore@driessen.com